



REGAL[®] CLASSIC

PREMIUM INTERIOR 100% ACRYLIC FLAT FINISH N215

Features

- High scrub formula
- New resin technology provides a beautiful flat finish
- Exhibits excellent touch-up characteristics
- Self priming on most surfaces
- Provides a mildew resistant coating
- Excellent Hide
- Painted surfaces can be washed after two weeks

Recommended For

Residential or commercial applications where a flat, high quality finish is desired. New or previously painted wallboard, plaster, masonry, or wallpapered surfaces; primed or previously painted wood or metal; new or coated acoustic ceilings.

General Description

A premium quality, proprietary 100% acrylic coating in a flat finish coupled with a low spatter formula that minimizes roller "overspray." It features easy application with no unpleasant paint odor, fast dry, and soap and water cleanup. An elegant and easy to apply, flat finish for ceilings and low traffic areas.

Limitations

- Do not apply when air and surface temperatures are below 50°F (10°C)

Product Information

<p>Colors:—Standard: White and a variety of ready-mixed colors</p>	<table border="1"> <thead> <tr> <th>Technical Data[◇]</th> <th>Pastel Base</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>Proprietary Acrylic Latex</td> </tr> <tr> <td>Pigment Type</td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td>35%</td> </tr> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td>400 – 450 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness</td> <td></td> </tr> <tr> <td>Recommended Film – Wet Thickness</td> <td>3.8 mils</td> </tr> <tr> <td>Recommended Film – Dry Thickness</td> <td>1.3 mils</td> </tr> <tr> <td colspan="2">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td>Dry Time @ 77° F (25° C) @ 50% RH</td> <td></td> </tr> <tr> <td>– To Touch</td> <td>1 Hour</td> </tr> <tr> <td>– To Recoat</td> <td>1 – 2 Hours</td> </tr> <tr> <td colspan="2">Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.</td> </tr> <tr> <td>Dries By</td> <td>Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity</td> <td>100 ± 3 KU</td> </tr> <tr> <td>Flash Point</td> <td>None</td> </tr> <tr> <td>Gloss / Sheen</td> <td>Flat</td> </tr> <tr> <td>Surface Temperature at Application</td> <td></td> </tr> <tr> <td>– Min.</td> <td>50° F</td> </tr> <tr> <td>– Max.</td> <td>90° F</td> </tr> <tr> <td>Thin With</td> <td>See Chart</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Clean Water</td> </tr> <tr> <td>Weight Per Gallon</td> <td>11.4 lbs</td> </tr> <tr> <td>Storage Temperature</td> <td></td> </tr> <tr> <td>– Min.</td> <td>40° F</td> </tr> <tr> <td>– Max.</td> <td>90° F</td> </tr> <tr> <td colspan="2">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td>95 Grams/Liter</td> <td>.79 lbs./Gallon</td> </tr> </tbody> </table>	Technical Data [◇]	Pastel Base	Vehicle Type	Proprietary Acrylic Latex	Pigment Type	Titanium Dioxide	Volume Solids	35%	Coverage per Gallon at Recommended Film Thickness	400 – 450 Sq. Ft.	Recommended Film Thickness		Recommended Film – Wet Thickness	3.8 mils	Recommended Film – Dry Thickness	1.3 mils	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.		Dry Time @ 77° F (25° C) @ 50% RH		– To Touch	1 Hour	– To Recoat	1 – 2 Hours	Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.		Dries By	Evaporation, Coalescence	Viscosity	100 ± 3 KU	Flash Point	None	Gloss / Sheen	Flat	Surface Temperature at Application		– Min.	50° F	– Max.	90° F	Thin With	See Chart	Clean Up Thinner	Clean Water	Weight Per Gallon	11.4 lbs	Storage Temperature		– Min.	40° F	– Max.	90° F	Volatile Organic Compounds (VOC)		95 Grams/Liter	.79 lbs./Gallon
Technical Data [◇]	Pastel Base																																																								
Vehicle Type	Proprietary Acrylic Latex																																																								
Pigment Type	Titanium Dioxide																																																								
Volume Solids	35%																																																								
Coverage per Gallon at Recommended Film Thickness	400 – 450 Sq. Ft.																																																								
Recommended Film Thickness																																																									
Recommended Film – Wet Thickness	3.8 mils																																																								
Recommended Film – Dry Thickness	1.3 mils																																																								
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.																																																									
Dry Time @ 77° F (25° C) @ 50% RH																																																									
– To Touch	1 Hour																																																								
– To Recoat	1 – 2 Hours																																																								
Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.																																																									
Dries By	Evaporation, Coalescence																																																								
Viscosity	100 ± 3 KU																																																								
Flash Point	None																																																								
Gloss / Sheen	Flat																																																								
Surface Temperature at Application																																																									
– Min.	50° F																																																								
– Max.	90° F																																																								
Thin With	See Chart																																																								
Clean Up Thinner	Clean Water																																																								
Weight Per Gallon	11.4 lbs																																																								
Storage Temperature																																																									
– Min.	40° F																																																								
– Max.	90° F																																																								
Volatile Organic Compounds (VOC)																																																									
95 Grams/Liter	.79 lbs./Gallon																																																								
<p>—Tint Bases: Benjamin Moore[®] Color Preview[®] Bases 1B, 2B, 3B & 4B</p>																																																									
<p>—Special Colors: Contact your Benjamin Moore representative</p>																																																									
<p>Certification:</p> <p>VOC Compliant in all regulated areas except the South Coast and areas of California that follow the 2007 Suggested Control Measures.</p> <p>Master Painters Institute MPI #53</p> <p>Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84</p>																																																									
<p>Technical Assistance</p> <p>Available through your local authorized independent Benjamin Moore[®] retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.</p>																																																									

[◇]Reported values are for Pastel Base. Contact Benjamin Moore for values of other bases or colors.

Regal® Classic Premium Interior 100% Acrylic Flat Finish N215

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure 30 days before applying base coat. Cured plaster should be hard, have a slight sheen and maximum PH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound.

Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming. Wood substrates must be thoroughly dry.

Difficult Substrates: Benjamin Moore offers a variety of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

Regal® Classic Finish is self priming on most surfaces. On bare substrates two coats are required; previously painted surfaces can be finished with 1 or 2 coats. While the high quality of our products sometimes makes one-coat coverage achievable, Benjamin Moore recommends two coats of this product to achieve full color development and to maximize paint film performance. **Special Note:** Certain deep custom colors may require a Deep Base Primer tinted to a special prescription formula to achieve the desired color. Consult your retailer.

Wood, and engineered wood products:

Primer: Regal® Classic Premium Interior Latex Primer (N216), Fresh Start® All-Purpose 100% Alkyd Primer (024) or Fresh Start® Alkyd Enamel Underbody (217)

Finish: 1 or 2 coats Regal® Classic Premium Interior 100% Acrylic Flat Finish (N215)

Bleeding woods; like redwood or cedar: Fresh Start® All-Purpose Alkyd Primer (024), Alkyd Enamel Underbody (217) or Fresh Start® 100% Acrylic Superior Primer (046)

Finish: 1 or 2 coats Regal® Classic Premium Interior 100% Acrylic Flat Finish (N215)

Drywall:

Primer/Finish: 1 or 2 coats of Regal® Classic Premium Interior 100% Acrylic Flat Finish (N215)

Plaster:

Primer/Finish: 1 or 2 coats of Regal® Classic Premium Interior 100% Acrylic Flat Finish (N215)

Rough or Pitted Masonry:

Primer: Super Spec® Latex Block Filler (160) or Super Spec® Masonry Interior/Exterior Hi-Build Block Filler (206)

Finish: 1 or 2 coats Regal® Classic Premium Interior 100% Acrylic Flat Finish (N215)

Smooth Poured or Pre-cast Concrete:

Primer/Finish: 1 or 2 coats of Regal® Classic Premium Interior 100% Acrylic Flat Finish (N215)

Ferrous Metal (Steel and Iron):

Primer: Super Spec HP® Acrylic Metal Primer (P04) or Super Spec HP® Alkyl Metal Primer (P06)

Finish: 1 or 2 coats Regal® Classic Premium Interior 100% Acrylic Flat Finish (N215)

Non-Ferrous Metal (Galvanized & Aluminum): All new metal surfaces must be thoroughly cleaned with Super Spec HP® Oil & Grease Emulsifier (P83) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion

Primer: Not required on properly prepared surfaces

Finish: 1 or 2 coats Regal® Classic Premium Interior 100% Acrylic Flat Finish (N215)

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Mixing of Paint: Stir thoroughly before and during use. Apply one or two coats. For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed.

Thinning/Cleanup

Conditioning with Benjamin Moore® 518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance		
	Mild conditions	Severe conditions
	Humid (RH> 50%) with no direct sunlight & with little to no wind	Dry (RH<50%), in direct sunlight, or windy conditions
Brush: Nylon / Polyester	No thinning necessary	Add 518 Extender or water: Max of 8 fl. oz. to a gallon paint Never add other paints or solvents.
Roller: Premium Quality Nylon/Polyester		
Spray: Airless Pressure: 1,500 or 2,500 psi Tip: 0.013-0.017		

Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental, Health & Safety Information

N216 80Contains: Crystalline Silica that can cause cancer when in respirable form (spray mist or sanding dust).

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: In case of eye contact, flush with water for 15 minutes; for skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to Material Safety Data Sheet for additional health and safety information.